



PLEASE NOTE THAT WE HAVE
INSTALL VIDEOS FOR MANY
MODELS ON GOOGLE VIDEO AND
YOUTUBE.COM. SEARCH UNDER
"WIND DEFLECTOR"

Wind Deflector PT Cruiser - 2005 to 2007 Installation Guide

START BY PUTTING YOUR TOP DOWN

STEP 1: REMOVE THE WIND DEFLECTOR FROM THE BAG AND PLACE IT IN THE BACK SEAT AREA, AS IT SITS BEHIND THE FRONT SEATS



STEP 2: START BY LINING THE PLASTIC SLIDER ON THE WIND DEFLECTOR UP WITH THE TOP OF THE ROLL BAR. THE STRAP WILL GO UNDER THE ROLL BAR



LOVE THE DRIVE COPYRIGHT 2007, WWW.LOVETHEDRIVE.COM PRINTED IN CANADA PAGE 1

STEP 2 CONT: THE STRAP WILL WRAP AROUND THE ROLL BAR THEN GOES THRU THE PLASTIC SLIDER



STEP 2 CONT: PULL THE STRAP SNUG AND THEN FOLD THE STRAP SO THE VELCRO ON EACH SIDE OF THE STRAP IS HOLD IT IN PLACE



STEP 2 CONT: REPEAT ON THE OTHER SIDE. YOU WILL LIKELY NEED TO MAKE SMALL ADJUSTMENTS TO THE STRAP TO GET AN EVEN LOOK, WITH NO WRINKLES



STEP 3: NOW ATTACH THE WIND DEFLECTOR TO THE BACK SEAT. USING THE SNAP AND THE BLACK HOOK THAT ATTACHES TO THE SIDE OF TRIM PANNEL



STEP 3 CONT: MAKE SURE THE BLACK HOOK ON THE ELASTIC IS PAST THE EDGE OF THE TRIM PANNEL AND HOOK TO THE LIP.



STEP 3: REPEAT ON THE OTHER SIDE THE ELASTIC AND HOOK WILL HOLD THE WIND DEFLECTOR IN PLACE



STEP 4: PUSH THE SNAP INTO PLACE (THIS SOMETIMES TAKES A LITTLE FORCE) REPEAT TO THE OTHER SIDE.



STEP 5: THE SIDE STRAP FOR THE WIND DEFLECTOR IS ATTACHED TO THE STEEL BRACKET ON THE SIDE OF THE QUARTER TRIM PANEL



STEP 5 CONT: ATTACH THE SILVER SNAP HOOKS TO THE THE STEEL BRACKETS WHICH ARE LOCATED ON THE TRIM PANEL BEHIND THE FRONT SEATS.



STEP 5 CONT. THE SIDE STRAP WILL HOLD THE WIND DEFLECTOR IN PLACE. REPEAT TO THE OTHER SIDE.



STEP 6: THE TOP OF SIDE STRAPS HAVE A BLACK PLASTIC END CLIP THAT WILL SNAP ON TO THE END CAP ON EACH END OF THE MIDDLE TUBES OF THE WIND DEFLECTOR



STEP 6 : THE END CAPS WILL THEN PULL THE WIND DEFLECTOR TIGHT. YOU MAY NEED TO ADJUST THE TOP STRAPS, ON THE ROLL BAR, TO GET THE WRINKLES OUT



**NOW YOU ARE READY TO LOVE THE DRIVE
WWW.LOVETHEDRIVE.COM**